

Now stocking the latest in CCD video camera imaging solutions. Our cameras literally deliver and clarity; and outstanding low light performance even in the presence of direct sunlight. IR camera, Waterproof camera, DVR (Upto to 16 channels), DVR cards, DVR Servers, PTZ camera and more.

BOX CAMERA



SPECIFICATION

- Color D/N Box Camera
- 1/3" Sony Ex-view HAD CCD,
 - C/CS Lens Mount, ALC(Video/DC)AGC
 - On(Low)/Off(High), AWB On/Off ,EE/AI Switch
 - BLC On/Off

KEY

- ALC (Auto-iris Lens Control), AGC (Auto Gain Control),
- AWB (Auto White Balance),
- Exposure Mode (EE: Eclectic Exposure/AI: Auto-iris),
- BLC (BackLight Compensation)

	CSP2120	CSP2130	CSP3120	CSP3130	CSP3140
LUX	0.03	0.01	0.8	0.5	0.5
TVL	420	480	420	480	480
VDC	12	12	12	12	12
COLOR	D/N	D/N	D	D	D/N

ZOOM CAMERA



Front side



Rear side

MODEL: CSP2130 / ZSP(P) 2720/2730

- 27X zoom Camera (420TVL/520TVL)
- 1/4" Sony Super HAD CCD, 420TVL
- 24X Optical zoom, Focus(AF/MF), OSD,
- RS-485 (Pelco-D)
- AGC, AWB, AWB, Auto Iris exposure,
- BLC On/Off, 12VDC

CCTV LENS



Fixed Focal Fixed Iris

MODEL

LF164F040	F1.6, f=4.0
LF164F060	F1.6, f=6.0
LF164F080	F1.6, f=8.0
LF164F120	F1.6, f=12
LF164F160	F1.6, f=16



Vari-Focal Auto Iris

MODEL

LV144D2812	F1.4, Auto Iris(DC), f=2.8mm~12mm
LV104D3008	F1.0 Auto Iris(DC), f=3.0mm~8.0mm
LV144D3508	F1.4, Auto Iris(DC), f=3.5mm~8.0mm
LV184D50100	F1.8, Auto Iris(DC), f=5.0mm~100mm
LV164D6060	F1.4, Auto Iris(DC), f=6.0mm~15mm
LV144D6015	F1.6, Auto Iris(DC), f=6.0mm~60mm



Vari-Focal Manual Iris

MODEL

LV144M2812	F1.4, Manual Iris, f=2.8mm~12mm
LV104M3008	F1.0, Manual Iris, f=3.0mm~8.0mm
LV144M3508	F1.4, Manual Iris, f=3.5mm~8.0mm
LV184M50100	F1.8, Manual Iris, f=5.0mm~100mm
LV164M6060	F1.4, Manual Iris, f=6.0mm~15mm
LV144M6015	F1.6, Manual Iris f=6.0mm~60mm

CAMERA HOUSING



HT-1110L, H(Heater),B(Blower)
HT-1110L-BH (Blower + Heater)



HT-1110M, H(Heater), B(Blower)
HT-1110M-BH (Blower + Heater)

	HT-1110L, H(Heater),B(Blower) HT-1110L-BH (Blower + Heater)	HT-1110M, H(Heater), B(Blower) HT-1110M-BH (Blower + Heater)
Material	Aluminum	Aluminum
Dimension	110(W) x 100(H) x 390(L)mm	110(W) x 110(H) x 340(L)mm
Suitable camera size	76(W) x 62(H) x 270(L)mm	76(W) x 62(H) x 220(L)mm
Control Temperature	Heater(ON : 15°C, OFF : 25°C); Blower(ON : 35°C, OFF : 25°C)	Heater(ON : 15°C, OFF : 25°C); Blower(ON : 35°C, OFF : 25°C)
Input Voltage	12VDC/24VAC/110VAC/220VAC	12VDC/24VAC/110VAC/220VAC

SPECIALITY CAMERAS



CSP3232-3P
Smoke Detector Type Camera



CSP3252(a)
Mini Camera (with audio)



CSP3252 (b)
Mini Camera



CSP3252 (c)
Bullet Camera (Weatherproof)
68mm X 27mm size w/ Bracket

MODEL

LUX	0.8	1.0	0.8	1.0
TVL	420	-	420	420
VDC	12	12	12	12
LENS	3.6mm	3.6mm	3.6mm	3.6mm